## MEASUREMENT OF ABSOLUTE ELECTRON CAPTURE CROSS SECTIONS FOR $7 \times q \ keV \ Fe^{q+}$ IONS IN COLLISIONS WITH $CO_2$

I. Čadež\* a, S. J. Smith\*, M. Niimura\*, J. B. Greenwood<sup>†</sup>, and A. Chutjian\*

\*Jet Propulsion Laboratory, California Institute of Technology, Pasadena, California, USA

†Physics Department, The Queen's University, Belfast, UK

Iron ions are important heavy ion constituents of the solar wind. These ions are present in highly charged states ranging from  $Fe^{7+}$  to  $Fe^{13+}$  with  $Fe^{10+}$  and  $Fe^{11+}$  being the most abundant<sup>1</sup>. Electron capture is an ion - molecule collision process which typically has a large cross section. Knowing its value for a particular ion/molecule pair is important for understanding the interaction of solar wind with comets and planetary atmospheres.

We have started a systematic experimental study of charge-changing cross sections for iron ions. The 14.0 GHz electron cyclotron resonance ion source (ECRIS), which is a key element of our highly charged ion facility<sup>2</sup>, allows us to obtain beam of all the above mentioned iron ions. For this purpose we are using ferrocene vapor  $C_{10}H_{10}Fe$  as the discharge-supporting gas.

For measurement of charge changing cross sections the retarding potential method is used for charge analysis of ions after they traverse the target-gas cell. The method is described elsewhere<sup>3</sup> and allows efficient study of collisional charge exchange. It can be used in three different ways:




Figure 1. M/q spectra for different retarding potentials: 6.8kV (light full line) and 7.2kV (filled-in peaks). Positions of  $^{56}Fe^{q+}$  and  $^{54}Fe^{q+}$  are indicated. The ion acceleration voltage was 7kV and the ECRIS microwave power was 28W.

(1) scanning the M/q spectra with low retarding field, and retarding field high enough to eliminate the parent ions. This allows fast screening of the charge changing efficiency for groups of ions at a fixed acceleration voltage. An example is shown in Fig. 1. (2) measurement of ion current variation with target gas pressure for different retarding fields. The low pressure slope determines the cross section. Its detailed shape reveals the presence of metastable ions in the incident beam. (3) consecutive measurement of transmitted current for a chosen ion and at fixed pressure, for different retarding fields. This affords the fastest determination of cross section at particular ion energy.

Electron capture cross sections for  $Fe^{q+}$  in  $CO_2$  were measured at  $7 \times q \ keV$  and for q from 5 to 11. Measurements in CO are in progress.

Acknowledgment: I. Čadež and M. Niimura thank the National Research Council for senior fellowships through the NASA-NRC program. This work was carried out at the Jet Propulsion Laboratory, California Institute of Technology and was supported by the National Aeronautics and Space Administration.

<sup>a</sup>On leave from Jožef Stefan Institute, Ljubljana, Slovenia

## References

- 1. R. Wegmann, H. U. Schmidt, C. M. Lisse, K. Dennerl and J. Englhauser, Planet.Space. Sci. **46**, 603 (1998).
- 2. A. Chutjian, J. B. Greenwood, and S. J. Smith, in Applications of Accelerators in Research and Industry (ed. J. L. Duggan and I. L. Morgan, AIP Conf. Proc.475, AIP, New York, 1999).
- 3. J. B. Greenwood, I. D. Williams, S. J. Smith, and A. Chutjian, Phys. Rev. A (in press); J. B. Greenwood, A. Chutjian, and S. J. Smith, Astrophys. J. **529**, 605 (2000).

E-mail: ara.chutjian@jpl.nasa.gov